

BLADE AND LETTERING SIZE REQUIREMENTS

SPEED (MPH)	BLADE SIZE	UPPER CASE LETTER HEIGHT	LOWER CASE LETTER HEIGHT	DIRECTION (N,S,E,W)	DESIGNATION (ST,DR,ETC..)	LETTER SPACING
25 OR LESS	8" HIGH	4"	3"	2 1/2"	1/2" SMALLER THAN LOWER CASE LETTER	1/2"
26 OR MORE	9" HIGH	5"	4"	3 1/2"		3/4"

PRIVATE STREETS SHALL BE AS SHOWN BELOW WITH A BLUE BACKGROUND IN PLACE OF GREEN

ADJUST BLADE LENGTH TO ACCOMMODATE LENGTH OF STREET NAME

TYPE:

FLAT DOUBLE FACED, .125 ALUMINUM
STREET NAME SIGN: HIGH INTENSITY REFLECTIVE PRISMATIC GRADE SHEETING

COLOR/DESIGN:
WHITE LETTERING ON GREEN WITH WHITE BORDER AS SHOWN.

NOTES:

MAINTAIN 9'6" OF CLEARANCE FROM THE BOTTOM OF THE LOWEST STREET SIGN TO FINISH GRADE

SLEEVE SHALL BE 30" - 12GA X 2 1/4" SQ. TUBE
POST SHALL BE 12GA X 2" SQ. TUBE

LOCATE POSTS SO TRAFFIC CONTROL SIGNS CAN BE PLACED ON THE SAME POST WITH PROPER CLEARANCE

DO NOT USE ABBREVIATIONS FOR STREET NAMES (MT. VIEW vs. MOUNTAINVIEW)

ALL SIGNS SHALL BE HIGH INTENSITY PRISMATIC GRADE SHEETING

